

# Professional Dishwashers

## PG 8056 & PG 8061



### The new generation of professional dishwashers

The world's fastest fresh water commercial dishwashers provide impeccable cleaning results, unmatched performance, and user friendliness. Miele's new dishwashers can run up to 40 cycles per day and can accommodate a large variety of baskets and inserts, including commercial plastic baskets. The PG 8056 and PG 8061 are equipped with an innovative, high-performance circulation pump and new spray arm design for even better cleaning results and reduced water consumption.

Both models are exclusively recommended by Riedel and are ADA compliant. The PG 8056 is ideal for homes, butler's pantries and offices while the PG 8061, with its final rinse temperature of 185° F, is ideal for applications requiring sanitization including wineries, nursing homes, inns, community kitchens, restaurants, schools and other businesses.

### The Miele difference at a glance

- Fastest cycle time as short as 6 minutes
- Large capacity and multi-level cleaning for high throughput
- Low noise emission - 59 db or less
- Special programs and cycles e.g. China & Crystal
- Built-in water softener



### Designed to last

The PG 8056 and PG 8061 fresh water dishwashers are designed to last at least 15,000 operating hours. If used 6 times a day, 6 days a week, the unit will last for more than 13 years.

Email [proinfo@mieleusa.com](mailto:proinfo@mieleusa.com) for a full brochure with information on all dishwasher models, baskets, inserts and accessories.



Various baskets and inserts available



Standard basket configuration

# Professional Dishwashers

## PG 8056 & PG 8061



Model	PG 8056		PG 8061	
<b>Design</b>				
Style	Undercounter		Undercounter	
Freestanding Conversion Kit	Optional		Optional	
Baskets	U 890 with 2 x E 816 and 2 x E 165, O 891 with 1 x E 810		U 890 with 2 x E 816 and 2 x E 165, O 891 with 1 x E 810	
Commercial Dish Racks	Optional		Optional	
Cutlery	Cutlery Holder		Cutlery Holder	
Door Panel	Stainless steel		Stainless steel	
<b>Performance Features</b>				
Fastest Cycle	6 mins		15 mins	
Max. Number of Recommend Cycles/Day	40		40	
Number of Programs	10		3	
<b>Convenience Features</b>				
AutoClose/ComfortClose			•	
AutoOpen			•	
EasyOpen	•			
Delay Start	•		•	
Automatic Liquid Detergent Dispenser Pump	Optional		Optional	
<b>Cleaning Features</b>				
Condenser/Auto Open Drying			•	
Built-In Water Softener	•		•	
Perfect GlassCare	•			
<b>Safety Features</b>				
Double WaterProof System	•		•	
<b>Approvals, Certifications and Compliance</b>				
ADA Compliant	•		•	
NSF Certified			Pending	
Riedel Exclusively Recommends	•		•	
<b>Technical Data</b>				
Dimensions	33" H x 24" W x 23" D		33" H x 24" W x 24" D	
Weight	154 lbs		160 lbs	
Water Connection	2 (hot and cold water)		3 (hot, cold, cold)*	
Noise Emission	59 db		57 db	
<b>Electrical Requirements</b>				
Model Number	61805650USA	61805655USA	61806120USA	61806125USA
Voltage	2 AC 208V	2 AC 240V	3 AC 208V (conv. 2 AC 208V)	3 AC 240V (conv. 2 AC 240V)
Rated Load	5.8 kW	5.8 kW	5.8 kW	5.8 kW
Circuit Breaker	30 A	30 A	3 x 20 A (30 A)	3 x 20 A (30 A)
Plug	NEMA L6-30	NEMA L6-30	NEMA L15-20 (NEMA L6-30)	NEMA L15-20 (NEMA L6-30)

\*Use supplied Y-connector if only one cold water connection is available