

WINE & SPIRITS PRODUCT BULLETIN



Experts in "What If..."

50# Aged Agave 100% PCW w/Wet Strength Label Stock

Wausau Coated Products introduces 50# Aged Agave made with Agave Sisalane fibers from reclaimed burlap coffee bean bags as a new facestock option. This process gives the sheet a smooth natural color and diverts used packaging from landfills. It is manufactured with wet strength properties to increase performance in moist conditions and carries FSC® certification. Aged Agave is a great choice for wine, spirits, high-end beverages and gourmet foods. This base sheet is manufactured Process Chlorine Free, and features H-318, an adhesive that provides excellent anchorage and provides outstanding performance. If you are looking for something unique for your brand, this is a great option.

- **W030343 ~ HP Indigo Optimized 50# Aged Agave, 100% PCW w/Wet Strength, FSC® Certified / H-318 / 1.2 mil Clear PET**

For additional product information and to request samples, visit our website at www.wausaucoated.com or contact our Customer Service Department at 800-345-8039.

FACESTOCK DESCRIPTION: 50# AGED AGAVE 100% PCW W/WET STRENGTH

This smooth natural tone paper has added Agave Sisalane fibers throughout the sheet for a unique appearance. It is manufactured with wet strength properties to increase performance in moist environments. It is suitable for high-speed bottling and packaging lines.

Basis Weight (25 x 38 /500), lbs.	50
Caliper, mils	4.2

ADHESIVE DESCRIPTION: H-318

H-318 is the ideal choice for high end beverage and spirits, with improved resistance to moisture and humidity after bottling. H-318 was engineered to provide excellent high initial tack and quicker label adhesion onto glass while providing functional converting performance on an array of facestocks. It is the adhesive of choice for textured and embossed/debossed labels.

Type	Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp °F	+35
Service Temperature Range °F	+10 to +150

LINER DESCRIPTION: 1.2 MIL CLEAR PET

A clear polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, mils	1.2
Yield, sq. in/lb	16,500
Tensile Strength, MD / TD, psi	29,900 / 29,900
Haze, %	3.5%
Elongation at break, MD / TD %	100 / 100
Shrinkage at 302 °F/30 min. MD / TD %	2 / 0.4
Regulatory Compliances	CONEG, REACH, RoHS

Shelf life: One year when stored at 72° F / 50% RH

Note: All product specifications are for informational use only. For more details visit wausaucoated.com
FSC® is a registered trademark of the Forest Stewardship Council®. FSC® C008943

